

Arizona LP



Standard equipment:

- 6.001.0089 Gun S'09 M22 with quick connection.



- 6.002.0322 Lance M22 with nozzle-holder.



- 5.012.0281 High pressure nozzle set (mod. 1209 LP)
- 5.012.0401 High pressure nozzle set (mod. 1311 LP)



- 4.618.0128 High pressure hose 8 m



- Power cable 5 m

Available versions:

Code: **8.665.0011**

Arizona 1209 LP **with hose-reel** (10 m high pressure hose)

Code: **8.665.0010**

Arizona 1311 LP **with hose-reel** (10 m high pressure hose)

VERSION
60 Hz
AVAILABLE
DETAILS PAGE 9

T.S. Total Stop

Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection.
- Three ceramic coated pistons, brass linear pump head with built-in by-pass valve.
- Suction and delivery S/S valves.
- Detergent built-in tank for indirect suction.
- Pressure regulator.
- Glycerine pressure gauge.
- Hose-reel (**optional**).
- Accessory holder.
- Hose-holder.
- Ergonomic handle.

	Arizona 1209 LP	Arizona 1311 LP
code	8.665.0001	8.665.0006
operat. pressure/max	120/150 bar-1740/2175 psi	130/150 bar-1885/2175 psi
delivery rate	510 l/h-2.23 GPM	660 l/h-2.90 GPM
abs. power/voltage	2300W - 230V~50Hz 1 ph	2900W - 230V~50Hz 1 ph
motorpump type/RPM	MP3/1450 RPM	MP3/1450 RPM
max. water inlet temperature	40 °C	40 °C