

Hyper 1600



Standard equipment:



- 5.511.1941 PP brush Ø 430 mm - 17"



- 4.508.1319 Front squeegee blade Shore 40 Th. 2,5 mm
- 4.508.1320 Rear squeegee blade Shore 40 Th. 3,0 mm



- 0.108.0073 On-board Battery charger 24V 10A (only for model code: 8.580.0021)

- Ideal for small and medium floors up to 1600sqm, especially when congested by people or furnishing like in wellness centres, gyms, car showroom, retail shops, hospitals and schools.
- Automatic brush attachment, discharge and delayed cut-off.
- Adjustable solution release with automatic cut-off.
- Narrow body with both side brush protrusion and 300° squeegee spin.
- Tool less removable recovery tank with large visual inspection window and stretchable discharge hose.
- Adjustable driving handle with dead man switches, soft touch controls and diagnosis (Eco Energy mode and battery low level automatic cut-off for DC version).
- Large non marking working wheels and sturdy rear roller for displacements.



Watch the video on youtube:
www.youtube.com/lavorpro

| | Hyper 1600E | Hyper 1600B |
|-----------------------------|-------------------------------|--------------------------------|
| code | 8.580.0022 | 8.580.0021 |
| power supply | 230V 50Hz | 24V (battery charger included) |
| scrubbing/squeegee width | 450/540 mm | 450/540 mm |
| max working capacity | 1600 m ² /h | 1600 m ² /h |
| solution tank capacity | 30 l/7.92 gal | 30 l/7.92 gal |
| recovery tank capacity | 32-35 l/8.45 - 9.24 gal | 32-35 l/8.45 - 9.24 gal |
| traction | mechanical | mechanical |
| RPM/pressure on the brushes | 150/18 kg/39,68 lbs | 150/18 kg/39,68 lbs |
| brush motor power | 300 W | 400 W |
| detergent solution system | solenoid valve | solenoid valve |
| depression/vacuum motor | 1200 mmH ₂ O/800 W | 1200 mmH ₂ O/400 W |
| dimensions/weight | 117x58x78 cm/66 kg | 117x58x78 cm/53 kg |