


 Walk behind machine  
with or without traction


 Battery autonomy  
2 - 4 h


 Operating tension  
24 V / 110 Ah

 Cleaning width  
500 mm

 Solution tank / recovery tank  
40 / 45 l

 Disc brush  
1 x 508 mm

 Brush pressure adjustable  
max. 30 kg

 Brush speed  
182 rpm



Theoretical working capacity

**1750/2000 m<sup>2</sup>/h**

Battery models, single brush, with 50 cm cleaning path.

The models differ from the presence or not of the traction system and for their accessories.


The brushes pressure is adjustable from the operator in function of the floor to be cleaned.

The semi-automatic models can be adjusted in the brushes inclination for easy driving.

The single brush system is equipped with the device of the brush coupling/uncoupling release without manual intervention and it is particularly suitable for small areas such as hospitals, schools, where a frequent sanitization of the brush is essential.

ruby models result to be extremely silenced thanks to the patented housing system of the suction motor.

## Technical data

|                                  |   |
|----------------------------------|---|
| Squeegee width                   | 770mm   |
| Brush motor                      | 600 Watt  |
| Type of drive                    | semi-automatic/automatic  |
| Maximum gradient                 | 2%  |
| Suction motor                    | 570 Watt  |
| Suction vacuum                   | 120 mbar  |
| Machine dimensions               |   |
| length                           | 1205 mm   |
| height                           | 1053 mm   |
| width without squeegee           | 535 mm  |
| Machine weight without batteries | 75 / 85kg   |
| Traction motor                   | -- / 120 Watt   |
| Movement speed                   | -- / 4 km/h   |
| Battery compartment              |   |
| length                           | 342 mm  |
| width                            | 350 mm  |
| height                           | 300 mm  |
| Class                            |  |
| Protection level                 | IP 23   |
| Noise level                      | 67,3 / <70 dB (A)   |

