

### Tekna LP



#### Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling. Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- Low voltage and delayed Total Stop.
- Suction and delivery S/S valves.
- Vertical burner with high thermal efficiency steel coil.
- Auxiliary motor for burner air-cooling and two ways fuel pump.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Low fuel lamp and cut off. Safety valve.
- Header tank and antiscaling device. Panel with analogic controls. Hose-reel **(optional)**.

#### Standard equipment:

- 6.601.0001 Gun PRO S'10 3/8" M with quick connection



- 6.602.0043 Lance 900 mm with quick connection.



- 3.103.0053 Nozzle type 060 (mod. 1515 LP)
- 3.103.0050 Nozzle type 045 (mod. 2015 LP)
- 3.103.0055 Nozzle type 070 (mod. 2021 LP)



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m

#### Optional:

- Hose-reel with brake (hose not included) cod.6.608.0010
- On request models with header tank and/or antiscaling device.
- Antiscaling LC-PRECAL (pcs. 4 x 5 lt.) cod. 3.697.0044

**VERSION**  
**60**  
**Hz**  
**AVAILABLE**  
**DETAILS PAGE 33**

	TEKNA 1515 LP	TEKNA 2015 LP	TEKNA 2021 LP
code	8.622.0901	8.622.0902	8.622.0921
operat. pressure	150 bar-2175 psi	200 bar-2900 psi	200 bar-2900 psi
delivery rate	900 l/h-3.96 GPM	900 l/h-3.96 GPM	1260 l/h-5.55 GPM
abs. power/voltage	5500W - 400V~50Hz 3ph	7300W - 230V~50Hz 1ph	9700W - 400V~50Hz 3 ph
motorpump type/RPM	MPW5/1450 RPM	MPW5/1450 RPM	MPW5/1450 RPM
max. temp. inlet/outlet	40/140 °C	40/140 °C	40/140 °C