

## Thermic 5 H

POWERED by  
**HONDA**



**T.V.** Thermal Valve

### Equipped with:


- Three ceramic coated pistons, brass axial pump head with built-in by-pass valve.
- Suction and delivery S. S. valves. 5 HP **Honda** GP 160 unleaded gasoline engine.
- Integrated detergent suction with external suction probe.
- Pressure regulator.
- Glycerine pressure gauge.
- Hose reel (**optional**).
- Suction hose with check valve (**optional**).
- Steel frame.
- Hose holder.
- 3,1 l gasoline tank.

### Standard equipment:

- 3.700.0036 Gun M22 - 3/8"



- 3.701.0027 Lance M22 high/low pressure



- 3.103.0048 Nozzle type 035



- 4.618.0049 High pressure hose 8 m



### Optional:

- 6.608.0007 High-pressure hose reel (hose not included)
- 5.012.0319 Suction hose with check valve



### Thermic 5H

|                        |                           |
|------------------------|---------------------------|
| code                   | 8.601.0107                |
| operat. pressure       | 160 bar-2320 psi          |
| delivery rate          | 570 l/h-2.51 GPM          |
| engine type/hp         | Honda GP 160/5            |
| pump type/RPM          | TPBH4/3000 RPM            |
| max. water inlet temp. | 40 °C                     |
| dimension/weight       | 70x59x97cm/37 Kg - 81 lbs |