PROFESSIONAL

Hot water high-pressure cleaner

LAVOR

NPX




Standard equipment:

• 3.700.0030 Gun M22 - 3/8" with rotating coupling.



• 3.701.0015 Lance M22 high/low pressure



• 3.103.0050 Nozzle type 045 (mod. 1211 XP)
• 3.103.0049 Nozzle type 040 (mod. 1813 XP)



• 4.618.0143 High pressure hose 10 m



• Power cable 5 m

Equipped with:

• Three ceramic coated pistons, brass axial pump head with built-in by-pass valve.
• Low voltage and delayed Total Stop.
• Suction and delivery S. S. valves.
• Vertical burner with high thermal efficiency steel coil.
• Temperature regulation gauge.
• Low fuel lamp.
• Safety valve.
• Detergent built-in tank (3 lt) for indirect suction.
• Pressure regulator.
• Glicerine pressure gauge.
• Panel with analogic controls.
• Heavy duty steel frame.
• Accessory holder.
• Two ways fuel pump.
• Hose reel with brake **(optional)**.

Optional:

• 6.608.0001 Hose reel with brake (hose not included)

	NPX 1211 XP	NPX 1813 XP
code	8.620.0601	8.620.0617
operat. pressure/max	120/150 bar-1740/2175 psi	180 bar-2610 psi
delivery rate	660 l/h-2.91 GPM	780 l/h-3.43 GPM
abs. power/voltage	3200W - 230V~50Hz 1ph	6300W - 400V~50Hz 3 ph
motorpump type/RPM	MPBX2/2800 RPM	MPBX2/2800 RPM
max. water inlet/outlet temp.	40/140 °C	40/140 °C
dimension/weight	94x65x90cm/97 Kg - 213 lbs	94x65x90cm/99 Kg - 217 lbs

PROFESSIONAL

+971 4 235 1979 sales@cleantech-gulf.com cleantech-gulf.com